

The Noxon range of pallet wrappers deliver robust system's to suit all warehouse environments and applications. The wrappers are available from economical semi-automatic systems to automatic and fully automated pallet wrapping conveyor systems.

- Equipped with remote control, it allows the operator to manage the operation without leaving the forklift.
- Automatic operation-film attach and-cut off
- Pre stretch unit for lower wrapping costs
- User friendly control panel
- Optional extras to suit all applications

**Freesby** *Vip*







:: Sydney 02 9604 7766    :: Melbourne 03 9465 1500    :: Brisbane 07 3277 2177

## Freesby<sup>®</sup> Vip

### Specifications

Turntable Height	77mm
Turntable Diameter	1800mm
Maximum film height roll	500mm
Maximum film roll diameter	300mm
Maximum load weight	2000kg
Maximum Load height	2100mm
<b>Film tension Pre-Stretcher</b>	
Version 11	Carriage with pre-stretch rollers at fixed percentage that may be changed by substituting the gears at the top of the rollers. Std pre-stretch 150% Pre-stretch configuration possible from 50% to 250%.
Version 12	Carriage with continuous-change electronic motor driven pre-stretch, adjustable through the panel. Film is dispensed automatically, electronically assisted, at variable speed depending on request. Pre-stretch configurations up to 300%.
Automatic film clamp	Yes
Automatic film cut-off	
Remote controlled	
Variable speed turntable	
Variable speed film carriage	
Power Requirements	240V x 10amps
Compressed Air	20 ltrs / min x 6 bar
Machine Dimensions	2790mm x 1759mm

### Optional Extras

			
Loading ramp for pallet jack	Winder for easy film threading	Top Platen for light and unstable load	Underground template to create a flush operation surface

:: Sydney 02 9604 7766    :: Melbourne 03 9465 1500    :: Brisbane 07 3277 2177